

LIS008195395B2

(12) United States Patent

Teng et al.

(54) SYSTEM FOR MONITORING, DETERMINING, AND REPORTING DIRECTIONAL SPECTRA OF OCEAN SURFACE WAVES IN NEAR REAL-TIME FROM A MOORED BUOY

(75) Inventors: Chung-Chu Teng, Slidell, LA (US);
Rodney Riley, Long Beach, MS (US);
Richard Bouchard, Gulfport, MS (US)

(73) Assignee: The United States of America as represented by the Secretary of

Commerce, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 373 days.

(21) Appl. No.: 12/554,910

(22) Filed: Sep. 6, 2009

(65) Prior Publication Data

US 2011/0060525 A1 Mar. 10, 2011

(51) Int. Cl. G01V 3/00

G01V 3/00 (2006.01) **G01V 7/00** (2006.01)

702/188; 702/191 Field of Classification Search 702/2, 45,

702/50, 76, 77, 141, 150, 151, 179, 188, 702/191; 324/76.19, 76.21; 73/170 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,301,047 A	1/1967	Von Wald, Jr.	
4,515,013 A	* 5/1985	Hue	73/170.01
4 986 121 A	1/1991	Luscombe	

(10) Patent No.: US 8,195,395 B2 (45) Date of Patent: Jun. 5, 2012

FOREIGN PATENT DOCUMENTS

JP 60149911 8/1985 JP 2005083998 3/2005

OTHER PUBLICATIONS

Teng et al., Determination of Pitch and Roll Angles from Data Buoys, 2004, IEEE, vol. 3, pp. 1348-1355.*

(Continued)

Primary Examiner — Michael Nghiem
Assistant Examiner — Yaritza H Perez Bermudez
(74) Attorney, Agent, or Firm — Robert Platt Bell

(57) ABSTRACT

A moored buoy floating at the ocean surface and anchored to the seafloor precisely measures acceleration, pitch, roll, and Earth's magnetic flux field of the buoy over a limited sampling period. The system includes: 1) A buoy, 2) A mooring system, 3) An electronic data logger controlling communications between the system and the on-board remote telecommunications system, 4) an embedded computer for data input/ output, temporary or permanent data storage, and algorithms to convert the measured time series data into surface ocean wave spectra and quality assurance statistics and encode the results for transfer to the data logger, 5) Sensors include one or three acceleration sensors, three orthogonal angular rate sensors, and three orthogonal magnetometers to measure the Earth's magnetic flux field, 6) A telecommunications system that links the buoy data logger and a shoreside processing system, and 7) A shoreside processing system that decodes the transmitted data, performs, quality control, and computes derived wave parameters.

18 Claims, 2 Drawing Sheets

